

FOMTEC ENVIRO USP

Fluorine Free Foam concentrate



Fomtec ENVIRO USP

Fomtec Enviro USP is a novel fluorine free firefighting foam totally free from fluorinated surfactants and polymers. Fomtec Enviro USP is especially designed to be an effective fluorine-free alternative for sprinkler systems, type II and III discharge devices.

- New Generation fluorine free foam
- Approved for sprinkler, type II and type III discharge devices to UL 162 & FM 5130
- Superior Fire Performance: Rate IA, EN 1568 Part 3.
- ICAO Level B
- For Class A & B fires
- 100% Biodegradable
- Low, Medium & High Expansion



FOMTEC ENVIRO USP

Fluorine Free Foam concentrate



DESCRIPTION

Fomtec Enviro USP can be used at 2% with fresh water for low, medium, and high expansion discharge devices. For sprinkler systems it should be used at 3% proportioning. For use on class A type fires induction ratio of 0.5-1% is recommended depending on application and discharge device.

Fomtec Enviro USP can be used with saltwater at 6% proportioning.

APPLICATION

Fomtec Enviro USP is intended for use on class B hydrocarbon fuel fires such as Oil, Diesel and Aviation fuels as well as class A fires such as wood, paper, textiles etc.

Fomtec Enviro USP is especially suited whenever a fluorine-free alternative with high fire performance is required.

Fomtec Enviro USP is approved for use in sprinkler systems as per UL listing and FM approval, or in systems designed for use with the product based on recommended minimum applications rates, application duration and discharge devices.

Fomtec Enviro USP is suitable for mobile firefighting by use of aspirating foam discharge devices such as foam branchpipes and monitors, where application rates and technique can be adjusted to the specifics of each incident.

SPRINKLER APPLICATION

Sprinkler applications are especially challenging for any foam due to the very low operating pressure and the very low expansion reached. Applying foam through a sprinkler is a very forceful application method and requires foam that can handle direct application and partial submersion into the fuel without losing its fire performance and burnback resistance. Foams that shall be regarded as suitable for Sprinkler applications shall also be able to withstand limited time of water deluge directly onto the foam blanket without losing its burnback properties. Fomtec Enviro USP has passed these tests showing superior extinguishing and burnback properties.

FIRE PERFORMANCE & FOAMING

The fire performance of this product has been measured and documented according to "International Approvals" stated in this document. The design parameters depend on type of system and application. The use of the product should follow design guidelines. The foaming properties are depending on equipment used and other variables such as water and ambient temperatures. Average expansion 7:1, average ¼ drainage time 25:00 minutes using UNI 86 test nozzle.

EQUIPMENT

Fomtec Enviro USP can easily be proportioned at the correct dilution using conventional proportioning equipment. The equipment should be designed to the foam type.

Fomtec Enviro USP should be used with the sprinklers it has been tested with as well as with discharge devices having expansion ratio and drainage time within tolerances of foam properties used in fire tests made with the product according to UL 162 and FM 5130.

COMPATIBILITY

Fomtec Enviro USP can be used together with foam compatible powders and other expanded foams.

It is only intended for use with fresh water.

Fomtec Enviro USP concentrate should not be mixed with other foam concentrates.

For material compatibility please refer to Fomtec Technical Advices FTA 20 addressing the topic. For material compatibility please refer to Fomtec Technical Advices FTA 20 addressing the topic.

TECHNICAL DATA	
Appearance	Clear to yellowish liquid
Specific gravity at 20°C	1.04 ± 0.01 g/ml
Viscosity	Pseudoplastic*
pH	6.5 – 8.5
Freezing point	-11°C
Recommended storage temperature	0°C to 55°C
Suspended sediment (v/v)	Less than 0.2%

*) See detailed viscosity data below

ENVIRONMENTAL

Fomtec Enviro USP is formulated using raw materials specially selected for their fire performance and their environmental profile. The product contains no intentionally added fluorinated surfactants, polymers, and other organohalogens. Fomtec Enviro USP is 100% biodegradable and contains no PFOS, nor PFOA. The handling of spills of concentrate or foam solutions should however be undertaken according to local regulations. Normally sewage systems can dispose foam solution based on this type of foam concentrate, but local sewage operators should be consulted.

Full details will be found in the Material Safety Datasheet (MSDS). For more detailed information please consult Fomtec Technical Advices FTA 40..

FOMTEC ENVIRO USP

Fluorine Free Foam concentrate



STORAGE / SHELF LIFE

Stored in original unbroken packaging the product will have a long shelf life. Shelf life in excess of 10 years will be found in temperate climates. As with all foams, shelf life will be dependent on storage temperatures and conditions.

For storage recommendations and material compatibility please refer to our Fomtec Technical Advices FTA 10 addressing the topic.

INSPECTION/TESTING/MAINTENANCE

The foam concentrate should be tested annually. The testing should be made by a suitable laboratory for analysis of foam concentrates and should measure: pH, specific gravity, expansion, drainage time. Storage containers should be inspected and reevaluated for the suitability of the storage location in regard to temperature fluctuations (temperature should be as stable as possible). Exposure to direct sunlight should be avoided

INTERNATIONAL APPROVALS

- UL 162, 8th Edition, topside and sprinkler
- FM 5130 topside and sprinkler
- EN 1568 Part 1, Pass
EN 1568 part 2, Pass
EN 1568 part 3, Class IA fresh water
- ICAO Level B
- GESIP approved for hydrocarbon fuels
- IMO 1312/MED at 6% for hydrocarbon and polar solvent fuels

PACKAGING

We supply this product in 25 litre and 5 US gallon cans, 200 litre and 55 US gallon drums, 1000 litre and 265 US gallon IBC containers and in bulk on special request.

Volume per piece	Packaging	Part no	Approx. Shipping weight*	Dimensions (mm) L x W x H
25 ltr	Can	11-6000-01	26.7 kg	295 x 260 x 441
200 ltr	Drum	11-6000-02	212.5 kg	581 x 581 x 935
1000 ltr	Container	11-6000-04	1080 kg	1200 x 1000 x 1150
5 US gal.	Can	11-6000-00	20.58 kg	295 x 260 x 441
55 US gal.	Drum	11-6000-03	220.66 kg	581 x 581 x 935
265 US gal.	Container	11-6000-05	1083.6 kg	1200 x 1000 x 1150
Bulk	Special request	11-6000-xx		

*including packaging

VISCOSITY DATA – FLOW CURVES

The viscosity flow curves are determined by Brookfield RST rheometer from low to high shear rates. The viscosity curves below are determined by calculating the average value of at least 8 different measurements and add a safety margin of three standard deviations to the average. The viscosity curves are determined for 20°C and 5°C. In the table below the kinematic viscosity (mm²/s) is calculated as dynamic viscosity (mPa·s) divided by the specific gravity of the concentrate.

ENVIRO BY FOMTEC

The Fomtec Enviro range comprises an extensive range of non-PFAS based foams suitable for use Emergency Response missions and System applications. Enviro foam concentrates are available for class A, class B fire hazards and products are available for low, medium, and high expansion discharge devices.



Shear Rate (s ⁻¹)	Dynamic Viscosity (mPa·s) 20°C	Dynamic Viscosity (mPa·s) 5°C	Kinematic Viscosity (mm ² /s) 20°C	Kinematic Viscosity (mm ² /s) 5°C
10.7	3728	3505	3584	3370
21.5	1939	1884	1864	1811
53.7	903	884	868	850
107.4	542	514	521	494
214.8	329	312	317	300
375.0	226	220	217	211
537.0	177	182	170	175
1074.0	145	142	139	137
1611.0	86	97	83	93
2148.0	70	82	68	79
2792.2	88	117	85	113

