











EXPLOSION VENTING SOLUTIONS

INNOVATIVE, PROVEN,

COST-EFFECTIVE

TECHNOLOGY



Authorised



Fike is the leader in delivering patented, innovative technologies to the explosion protection market. With over 65 years of field experience, Fike understands the complexities of plant processes, relevant code compliance and the critical nature of continued plant operation.

Proven to be one of the most effective forms of passive explosion protection, explosion venting provides overpressure protection from potential deflagration hazards by providing a planned pathway for the expanding gases to escape. Fike is a leader in the development of effective, cost efficient, ATEX certified explosion venting solutions. Economically priced and offering a long service life, Fike's wide range of explosion venting solutions are ideal for many applications.

Fike Explosion Vents

- Require little to no maintenance
- Proven to perform as designed and all models' performance is validated using large scale explosion tests
- Engineered to provide optimal performance characteristics:
 - Low mass
 - Cyclic pressure capability
 - Vacuum resistance
 - High venting efficiency
 - Certified burst pressures (P_{STAT})
- Full opening, non-fragmenting vent design, eliminating restraints
- No moving parts for greater reliability
- · Low product cost, simple installation, and long service life
- Weather covers, burst indicators, insulation and vacuum bar options available

Fike Explosion Protection Vents Product Overview

Protection against vessel collapse due to vacuum pressure

СОМРО	SITE EXPLOSION VENTS	Burst Pressure Range	Operating Ratio	Non- Fragmentin	Vacuum g Rating	Pulsating/ Cyclic	Explosion Vent Stocking Program	
	CV Simple, reliable Long lasting in static to light pressure cycling conditions Round and square/rectangular configurations	0.5 - 10.0 PSIG 35 - 690 MBARG	60 - 75%	Yes*	Partial	Good	Yes	Fike's Sto added ac
\bigcirc	CV-S High performance vent Superior service life for pressure cycling/pulsating conditions Round and square/rectangular configurations	1.0 - 15.0 PSIG 69 - 1030 MBARG	80 - 90%	Yes*	Full	Best	Yes	When yo shipmen manufac
	CV-SF Withstands full vacuum conditions with use of backup bars Long lasting in static to light pressure cycling conditions Round and square/rectangular configurations	0.5 - 10.0 PSIG 35 - 690 MBARG	60 - 75%	Yes	Full	Good	Yes	Select from in multiple CV -
	CV-CF Extended service life under heavy pulsating and cycling conditions For use in higher vibration applications Round and square/rectangular configurations	0.75 - 10.0 PSIG 52 - 690 MBARG	60 - 75%	Yes*	Partial	Best		
	CV-I Insulation extends service life in high temperature applications Round and square/rectangular configurations CV-SI	0.5 - 15.0 PSIG 35 - 1030 MBARG	60 - 75%	Yes	Partial	Good		CV-S -
	Insulation extends service life in high temperature applications Superior service life for pressure cycling/pulsating conditions Round and square/rectangular configurations	0.7 - 15.0 PSIG 50 - 1030 MBARG	80%	Yes	Full	Better		CV-SF -
SANITARY EXPLOSION VENTS								VMAX -
	SANI-VS Stable performance over a wide range of temperatures Integrated frame design for easy installation CIP/SIP; FDA compliant materials	0.3 -10.2 PSIG 21 - 703 MBARG	80%	Yes	Partial	Best		TIME IS N
1011	SANI-VSA 3-A and EHEDG Certified; Designed for clean production environments Integrated frame design for easy installation Sanitary gasket; FDA compliant materials	0.3 -10.2 PSIG 21 - 703 MBARG	80%	Yes	Partial	Best		STOCK EX
-	SANI-V [®] Versatile, economical Integrated frame design for easy installation CIP / SIP; FDA compliant materials	0.5 - 6.5 PSIG 35 - 448 MBARG	50%	Yes	Partial	Good		Vent
-	SANI-VA 3-A and EHEDG Certified Integrated frame design for easy installation Sanitary gasket; FDA compliant materials	0.5 - 6.5 PSIG 35 - 448 MBARG	50%	Yes	Partial	Good		• High qu variety
	CV-H Liner on process side supports hygienic applications Simple, reliable; Long lasting in static to light pressure cycling conditions Round and square/rectangular configurations	0.5 -15.0 PSIG 35 -1030 MBARG	60 - 75%	Yes		Good		• Easy pla BURST
HIGH PERFORMANCE / SPECIAL APPLICATION EXPLOSION VENTS								• An opti
Enco	VMAX [™] Stable performance over a wide range of temperatures	0.5 - 5.0 PSIG 35 - 345 MBARG	80%	Yes	Partial	Best	Yes	INSULA help av
	ELEGUARD [®] Designed specifically to protect bucket elevators Integrated frame designed for easy installation	0.7 - 2.9 PSIG 50 - 200 MBARG	25%	Yes		Good		reduce
	FLEX-V [®] Recloses, recovering 90% of vent relief area for more efficient use of firefighting agents; Reduces the risk of secondary explosions Protection against vessel collapse due to vacuum pressure	1.23 - 1.81 PSIG 85 - 125 MBARG	50%	Yes	Full	Good		• PROTE corrosio covers

*Larger diameters may require the optional High Integrity model to prevent fragmentation. Please consult factory.

Vent Stocking Program

Stock Explosion Venting Program gives you the advantages of quick turn-around and reduced costs. you select one of the listed stock vents, you realize ent within 48 hours*, at a price less than a custom actured vent. *Stock program varies by market

rom the following venting solutions, each available ole sizes.

- Provides excellent service life for static to light pressure cycling conditions and light vacuum conditions.
- Optimal for full vacuum process conditions with some pulsating/cycling. (currently available on round version only)
- Supports full vacuum conditions with use of back-up bars in the frame assembly.
- Multi-domed, high performance explosion vent provides excellent service life in challenging process conditions, stable performance over a
- wide range of temperatures and is vacuum rated.

MONEY, AND YOU SAVE BOTH WITH FIKE'S GLOBAL EXPLOSION VENT PROGRAM

Accessories

quality installation FRAMES are available in a

ty of materials and designs.

plant-wide monitoring with ST INDICATORS.



ptional ATMOSPHERIC

LATION pack is available to

avoid energy loss or condensation effects, and to ce acoustic emission levels of protected systems.

PROTECTION WEATHER COVERS are lightweight, corrosion resistant environmental protection. Weather covers minimize the effect of dirt, wind, snow, etc., while safeguarding the operation of the explosion vent.

Flameless Explosion Venting

During normal venting, an explosion is freely discharged, allowing flames and dust to exit the process vessel being protected. When the process vessel is located indoors, ducts are generally used to safely convey the explosion outside the building. However, ductwork has disadvantages and may result in decreased venting efficiency. Flameless venting, in combination with Fike explosion vents, can extinguish the flame from the vented explosion without the use of expensive ducting, limitations to equipment location, or more costly explosion protection.





- Eliminates need for expensive ducts
- Enhanced venting efficiency over venting with ductwork
- Virtually maintenance free

Highly suited for indoor applications, flameless venting is designed to protect people and equipment from flames and dust, releasing post-combustion gases only.



FlamQuench II[™]

- For use with round vents
- Field refurbish kits available
- FM/CE Approvals



FlamQuench SQ

- · For use with rectangular vents
- Field refurbish kits available
- CE Approvals



EleQuench® • For use with EleGuard explosion vents

CE Approvals

Testing Services

Every application, process and facility is unique and requires a complete assessment to determine what needs to be protected and the most effective means for accomplishing the safety goals. Fike offers a wide range of both standard and non-standard explosibility tests designed to assist companies in identifying and mitigating costly explosion hazards — all completed at Fike's own state-of-the-art testing laboratories.

Fike offers full-scale hazard explosion testing

- Define the characteristics of an explosion hazard in your plant
- Identify vulnerable process areas
- Design prevention and protection safety measures

Contact Fike for a hazard evaluation.



CONTACT FIKE

Fike is a global team of

experienced professionals

dedicated to life and

business safety. We work

closely with our clients to

solve highly complex

problems with easy-to-use

products and services.

FIKE GLOBAL MANUFACTURING, SALES AND SERVICE

AMERICAS

FIKE CORPORATION Blue Springs, MO, USA Tel: +1-816-229-3405 Email: industrial protection@fike.cc

FIKE CANADA Burlington, Canada Tel: +1-905-681-3100 Email: fikecanada@fike.com

FIKE LATINA LTD (MERCOSUR) Jundiai, Brazil Tel: +55-11-4525-5900 Email: vendas@fike.com.br

CARIBBEAN, CENTRAL, SOUTH AMERICA Houston, TX, USA Tel: +1-281-895-0756 Email: ccsasales@fike.com

ASIA

FIKE ASIA PACIFIC SDN BHD Selangor Darul Ehsan, Malaysia Tel: +60-3-7859-1462 Email: fikeap@fike.com

FIKE JAPAN Tokyo, Japan Tel: +81-335-951-291 Email: office@fikejapan.co.jp

FIKE INDIA PVT. LTD. Pune, India Tel: +91 020-64701025 Email: sameerp@pn2.vsnl.net.i

EUR OPE

FIKE EUROPE Herentals, Belgium Tel: +32-14-210031 Email: fike-europe@fike.com

FIKE UNITED KINGDOM Maidstone, Kent, United Kingdom Tel: +44-1-622-677081 Email: sales@fike.co.uk

FIKE FRANCE Cergy Pontoise Cedex, France Tel: +33-1-30-31-31-32 Email: contact@fike.fr

FIKE DEUTSCHLAND Mannheim, Germany Tel: +49-621-321-67-0 Email: info@fike.de

FIKE ITALIA Milano, Italy Tel: +39-02-2952-4166 Email: webmaster@fike.it

FIKE IBERICA Barcelona, Spain Tel: +34-93-6000-800 Email: fike@fike.es

MIDDLE EAST

FIKE CORPORATION DUBAI Dubai, UAE Tel: +971 4 3866455 Email: fike.dubai@fike.com











Unit 1/251 Ferntree Gully Road, Mt. Waverley, VIC 3149 P.O. Box 75, Mt. Waverley, VIC 3149 www.fire-protection.com.au

1300 742 296

Melbourne - Brisbane - Sydney - Perth - Auckland - Singapore - Kuala Lumpur