



GASOLINE FUME DETECTOR

G-1B-R | G-1B-24-R
G-1BB-R | G-1BB-24-R
G-1CB-R | G-1CB-24-R



Detect gasoline leaks early to prevent personal injury and possible explosions. Automatic blower control available.

ON BOARD, ON GUARD!®

PACKAGE CONTENTS:

- Gasoline Detector
- Fuel Sensor
- Extension Cable, 20 ft. (6 m)
- Relay ("BB" Blower Control Only)
- Manual

INSTALLATION:

- 1 Drill a 2-1/16 in. (52 mm) round hole
- 2 Install helm display through the hole and secure with threaded mounting nut
- 3 Mount sensor & plug in extension cable
- 4 Wire to existing blower (18 A maximum)
- 5 Connect power and ground wires to a 12 or 24V DC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with Sensor for Gasoline Powered Vessels
- ▶ 2-3/16 in. (56 mm) Round Black or Chrome Bezel with LEDs & Silence/Test Button
- ▶ Built in Blower Control Available
- ▶ Alarm will Sound and Red LED will light at 20% of the LEL
- ▶ Simple Installation
- ▶ 9-18 or 18-30V DC
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ Reverse Polarity Protected
- ▶ Current Draw @ 12V DC:
 - Nominal: 55 mA
 - Maximum: 95 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable fire detection and fire suppression products in addition to gas detection and control systems.

Pre-engineered and custom engineered fire suppression systems are available.



UNITED SAFETY
& SURVIVABILITY CORPORATION™

FIREBOY - XINTEX



1300 742 296

www.fire-protection.com.au



GASOLINE FUME DETECTOR

WITH or WITHOUT BLOWER CONTROL

G-2B-R
G-2BB-R
G-2BB-24-R



Detect gasoline leaks early to prevent personal injury and possible explosions. Automatic blower control available.

ON BOARD, ON GUARD!®

PACKAGE CONTENTS:

- Gasoline Detector
- (2) Fuel Sensors
- (2) Extension Cables, 20 ft. (6 m)
- Relay ("BB" Blower Control Only)
- Manual

INSTALLATION:

- 1 Drill a 2-1/8 in. (54 mm) round hole
- 2 Install helm display through the hole and secure with threaded mounting nut
- 3 Mount sensors & plug in extension cables
- 4 Wire to existing blower (18 A maximum)
- 5 Connect power and ground wires to a 12 or 24V DC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with (2) Gasoline Sensors
- ▶ 2-5/8 in. (67 mm) Square Black Bezel with LEDs & Silence/Test Button
- ▶ Alarm will Sound and Red LED will light at 20% of the LEL
- ▶ Built in Blower Control Available with 2 Sensors
- ▶ Simple Installation
- ▶ 9-18 or 18-30V DC
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ Reverse Polarity Protected
- ▶ Current Draw @ 12V DC:
 - Nominal: 95 mA
 - Maximum: 150 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection** and **control systems**.

Pre-engineered and custom engineered fire suppression systems are available.



UNITED SAFETY
& SURVIVABILITY CORPORATION™

FIREBOY - XINTEX



1300 742 296

www.fire-protection.com.au

PRODUCTS:

Gaseous Suppression



Inert Gas (IG-01, IG-55, IG-100, IG-541)
Novec 1230™ Fluid (FK-5-1-12)
FM-200® / NAF S 227 (HFC-227ea.)
Ecaro 125® / NAF S 125 (HFC-125)
Carbon Dioxide (CO₂)
Hybrid Systems (N₂ / Water)
Pressure Relief Vents
Enclosure Integrity Testing Equipment
Pipe & Fittings

Water Suppression



Water Mist - High Pressure
Water Mist - Intermediate Pressure
Water Mist - Low Pressure
Hybrid Systems (Water / N₂)
Monitors & Delivery Systems
High Speed Deluge

Foam Suppression



Foam Concentrates
Foam Proportioning
Foam Delivery Systems
Foam Concentrate Testing

Explosion Protection



Explosion Suppression
Explosion Isolation
Explosion Vents & Pressure Relief
Spark Suppression
Explosibility Testing

Fire Detection



Linear Heat Detection - Digital
Linear Heat Detection - Fibre Optic
Linear Heat Detection - Micro Chip
Flame Detection
Video Imaging Detection
Spark Detection
Control & Indicating Equipment
Thermal Imaging Detection
Aspirating Smoke Detection

Military & Defence



Military Vehicles
Naval Vessels

Special Applications



Micro Environment
Oxygen Reduction
Kitchen Protection Systems
Dry Chemical
Vehicle Systems
Compressed Air Foam
Marine & Offshore Vapour
Mitigation
Lithium-Ion Fire Systems

Support Services



Design / Engineering
Technical Support
Services & Testing

Australia

Head Office

Unit 1, 251 Ferntree Gully Road
Mt Waverley VIC 3149
Australia

Brisbane Office

Unit 7, 93 Rivergate Place
Murarrie QLD 4172
Australia

Perth Office

18 – 20 Ledger Road
Balcatta WA 6021
Australia

Sydney Office

Unit 5, 11 Reliance drive Tuggerah
NSW 2259
Australia

1300 742 296

www.fire-protection.com.au

New Zealand

Auckland Office

Unit 2, 13 Airborne Road
Albany North Shore 0632
New Zealand
www.fire-protection.net.nz

South East Asia

Regional Head Office

14 Gul Ave,
Singapore, 629657
www.fire-protection.com.sg



'Every solution for your special hazard problems'