

Splice Box for Sensor Cable “Metal Free”

Part number: 28024031



Specifications	
General description	Splice box for metal-free loose tube sensor cable of 4mm diameter “metal free”. Installation in control cabinet close to OTS. Can also be used as joint box for repairing metall-free sensor cable on location. Provides one entry for sensor cable and one entry for pigtail cable.
Included items	Splice cassette with cover, heat shrinking and crimp protection sleeve holder, preinstalled in box
Sensor cable entry	Cable gland for cables of 2.5 – 5.5mm diameter, wrench size 20mm. Optional for cables of 5 – 9mm diameter when removing gland reducer.
Pigtail cable entry (to OTS)	Cable gland for cables of 2.5 – 5.5mm diameter, wrench size 20mm. Optional for cables of 5 – 9mm diameter when removing gland reducer.
Material box	Polycarbonate, halogen free
Colour box	grey, RAL7035
Outer dimensions box (WxDxH)	240mm x 160mm x 90mm
Mounting box	4 holes in corners, 4.2mm diameter, distances: 228/130mm
Protection grade box	IP65
Weight	1.2kg
Storage / operating temperature	-40°C to 80°C
Compliances	RoHS, Box: UL94-V2

LIOS Technology GmbH
LINEAR OPTICAL SENSORS
Schanzenstrasse 39
Building D9-D13
51063 Köln/Cologne Germany
Tel.: +49 221 99887-0
Fax: +49 221 99887-150
info@lios-tech.com

Further information about our products and services can be obtained at our internet site www.lios-tech.com

MEMBER OF THE NKT GROUP

This document and all its components is protected by copyright. The recipient shall recognise these rights and shall not disclose the contents, either in whole or in part, of this document without the approval of the publisher to any other third party or use it for any other than its designated purpose