



PROPANE FUME DETECTOR

WITH DISPLAY, SENSOR & SOLENOID

P-1BS-R | P-1BS-24-R | P-1CS-R
P-1CS-24-R | P-1BNV-R | P-1CNV-R



Detect propane leaks early and automatically shut off gas supply to prevent personal injury and possible explosions.

ON BOARD, ON GUARD![®]

PACKAGE CONTENTS:

- Xintex Propane (LPG) Detector
- Fuel Sensor
- Extension Cable, 20 ft. (6 m)
- Solenoid Valve (Except "NV" Models)
- 3/8 in. x 1/4 in. Adapter
- Manual

INSTALLATION:

- 1 Drill a 2-1/16 in. (52 mm) round hole
- 2 Install helm display through the hole and secure with threaded mounting nut
- 3 Mount sensor & plug in extension cable
- 4 Install and wire solenoid valve to display
- 5 Connect power and ground wires to a 12 or 24V DC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with Sensor & Solenoid for Propane (LPG)
- ▶ Alarm will Sound & Red LED will light at 20% of the LEL
- ▶ Simple Installation
- ▶ 2-3/16 in. (56 mm) Round Black or Chrome Bezel with LEDs & Silence/Test Button
- ▶ 9-18 or 18-30V DC
- ▶ Solenoid Valve & Adapter (Except "NV" Models)
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ Solenoid Valve Control Button
- ▶ Reverse Polarity Protected
- ▶ "NV" Models Automatically Closes Solenoid Valve in Alarm Condition
- ▶ Current Draw @ 12V DC: - Nominal: 55 mA - Maximum: 725 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable fire detection and fire suppression products in addition to gas detection and control systems.

Pre-engineered and custom engineered fire suppression systems are available.

MADE IN THE USA





PROPANE FUME DETECTOR & ALARM WITH TWO SENSORS & SOLENOID VALVE

P-2BS-R
P-2BNV-R



Detect propane leaks early and automatically shut off gas supply to prevent personal injury and possible explosions.

ON BOARD, ON GUARD!®

PACKAGE CONTENTS:

Xintex Propane (LPG) Detector
(2) Fuel Sensors
(2) Extension Cables, 20 ft. (6 m)
Solenoid Valve ("BS" Only)
3/8 in. x 1/4 in. Adapter ("BS" Only)
Manual

INSTALLATION:

- ① Drill a 2-1/8 in. (54 mm) round hole
- ② Install helm display through the hole and secure with threaded mounting nut
- ③ Mount sensors & plug in extension cables
- ④ Install and wire solenoid valve to display
- ⑤ Connect power and ground wires to a 12 or 24V DC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with (2) Sensors & Solenoid ("BS" only) for Propane (LPG) will light at 20% of the LEL
- ▶ 2-5/8 in. (67 mm) Square Black Bezel with LEDs & Silence/Test Button
- ▶ Solenoid Valve & Adapter ("BS" only)
- ▶ Solenoid Valve Control Button
- ▶ Automatically Closes Solenoid Valve in Alarm Condition
- ▶ Alarm will Sound & Red LED
- ▶ Simple Installation
- ▶ 9-18 or 18-30V DC
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ Reverse Polarity Protected
- ▶ Current Draw @ 12V DC:
 - Nominal: 95 mA
 - Maximum: 780 mA

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection and control systems**.

Pre-engineered and custom engineered fire suppression systems are available.



MADE IN THE USA



**UNITED
SAFETY**

& SURVIVABILITY
CORPORATION™

FIREBOY - XINTEX



fire protection
TECHNOLOGIES



PRODUCTS:

Gaseous Suppression



Inert Gas (IG-01, IG-55, IG-100, IG-541)
Novec 1230™ Fluid (FK-5-1-12)
FM-200® (HFC-227ea.)
Carbon Dioxide (CO₂)
Hybrid Systems (N₂ / Water)
Pressure Relief Vents
Enclosure Integrity Testing Equipment
Pipe & Fittings

Water Suppression



Water Mist - High Pressure
Water Mist - Intermediate Pressure
Water Mist - Low Pressure
Hybrid Systems (Water / N₂)
Monitors & Delivery Systems
High Speed Deluge

Foam Suppression



Foam Concentrates
Foam Proportioning
Foam Delivery Systems
Foam Concentrate Testing

Explosion Protection



Explosion Suppression
Explosion Isolation
Explosion Vents & Pressure Relief
Spark Suppression
Explosibility Testing

Fire Detection



Linear Heat Detection - Digital
Linear Heat Detection - Fibre Optic
Linear Heat Detection - Micro Chip
Flame Detection
Video Imaging Detection
Spark Detection
Control & Indicating Equipment
Thermal Imaging Detection
Aspirating Smoke Detection

Military & Defence



Military Vehicles
Naval Vessels

Special Applications



Micro Environment
Oxygen Reduction
Kitchen Protection Systems
Dry Chemical
Vehicle Systems
Compressed Air Foam
Marine & Offshore
Vapour Mitigation
Li-Ion Fire Systems

Support Services



Design / Engineering
Technical Support
Services & Testing

Australia

Head Office

Unit 1, 251 Ferntree Gully Road
Mt Waverley VIC 3149
Australia

Brisbane Office

Unit 7, 93 Rivergate Place
Murarrie QLD 4172
Australia

Perth Office

18 – 20 Ledger Road
Balcatta WA 6021
Australia

Sydney Office

Unit 5, 11 Reliance drive Tuggerah
NSW 2259
Australia

1300 742 296

www.fire-protection.com.au

New Zealand

Auckland Office

Unit 2, 13 Airborne Road
Albany North Shore 0632
New Zealand
www.fire-protection.net.nz

South East Asia

www.fire-protection.com.sg



'Every solution for your special hazard problems'