

## IR3-H2 Triple IR Hydrogen Flame Detector

The IR3-H2 flame detector provides ultra-fast response, high performance and reliable detection of hydrogen fires. The detector addresses slow growing fires as well as fast eruptions of fire using improved IR3 technology. The detector operates in all weather and light conditions.

These features, along with the built-in event logger, provide additional means to study the cause and development of fire events.

### KEY BENEFITS

- High immunity to false alarm
- Ultra-fast detection mode detection within 40 milliseconds for Hydrogen fireballs or explosions
- Hydrogen flame detection
- High sensitivity – up to 100 ft. (30m)
- Data/Event logger – alarms, faults and other relevant events are logged to non-volatile memory
- Built-in-Test (BIT) – Automatic and manual internal self-test of window cleanliness and the overall operation of the detector
- Window heater to avoid condensation and icing
- Tilt mounting bracket can be connected either above or below the detector



### ORDERING

<b>FIK-IR3-H2-AS11<sup>1</sup></b>	Detector with M25 conduit openings
<b>FIK-IR3-H2-AS21<sup>1</sup></b>	Detector with ¾" NPT conduit openings
<b>FIK-TMO-S01<sup>2</sup></b>	Tilt Mount, Stainless Steel (shown above)
<b>FIK-FSIM-IR3-H2-KIT<sup>2</sup></b>	Flame Simulator Kit
<b>FIK-USB/RS485<sup>2,3</sup></b>	RS-485 to USB Converter Kit
<b>FIK-WCO-S01<sup>2,4</sup></b>	Weather Cover, Stainless Steel

<sup>1</sup> ATEX compliant models available. Contact Fike at 1-800-979-3453 for ordering information.

<sup>2</sup> Ordered separately.

<sup>3</sup> Converts detector RS-485 communication network to USB for connection to a computer port.

<sup>4</sup> Used only in very hot or very cold environments.

## SPECIFICATIONS

<b>FIRE DETECTION</b>	<b>Detection time and distance</b>	40ms for fast burst of explosion 1.5s for 32" (0.8m) hydrogen fire at 0-66 ft. (0-20m) 4s for 32" (0.8m) hydrogen fire at 66-100 ft. (20-30m)
	<b>Field of view (IR detection)</b>	90° Horizontal, 75° Vertical
	<b>Time Delay</b>	0-30 seconds (adjustable)
	<b>Built in Test</b>	Automatic or Manual
<b>ELECTRICAL SPECIFICATIONS</b>	<b>Operating Voltage</b>	24 VDC nominal (18-32 VDC)
	<b>Current Consumption</b>	Standby: 120mA Maximum: 180mA all systems in operation (including window heater)
	<b>Conduit Entries</b>	2X conduit entries ¾" 14NPT or M25x1.5
	<b>Wiring</b>	12-20AWG (2.5-0.35mm <sup>2</sup> )
<b>OUTPUTS</b>	<b>Relays</b>	Volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	<b>0-20mA (stepped) current output</b>	3 wire and 4 wire (isolated) configurations (sink and source)
	<b>Indication</b>	Tri-color LED
	<b>Modbus</b>	RTU compatible on RS-485
<b>MECHANICAL SPECIFICATIONS</b>	<b>Size</b>	5.51 x 3.54 x 3.54" (140 x 90 x 90 mm)
	<b>Weight</b>	Detector (stainless steel 316): 6.6 lbs. (3.0 kg) Tilt mount (stainless steel 316): 3.3 lbs. (1.5 kg)
<b>ENVIRONMENTAL SPECIFICATIONS</b>	<b>Temperature Range</b>	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	<b>Humidity</b>	Up to 99% (RH), non-condensing
	<b>Ingress Protection</b>	IP66 & 68 (2m, 24hr); NEMA 4X & 6P
<b>APPROVALS*</b>	<b>IECEX</b>	Ex db IIC T5 Gb -50°C ≤ Ta ≤ 75°C Ex db IIC T4 Gb -50°C ≤ Ta ≤ 85°C
	<b>FM &amp; FMC</b>	Class I, Div. 1, Groups B, C & D: T4 Class I, Zone 1, AEx/Ex db IIC T4 Gb T4 -50°C ≤ Ta ≤ 85°C T5 -50°C ≤ Ta ≤ 75°C
	<b>Performance</b>	ANSI FM 3260
	<b>WARRANTY</b>	<b>5 Years</b>

\*All products designed and tested to relevant approval standards.

## IMMUNITY TO FALSE ALARMS

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric arc	3.0 (1.0)	No Alarm	3.0 (1.0)	No Alarm
Arc welding	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Radiation heater, 2000W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Halogen lamp (1000W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Halogen lamp (500W) non-shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Exhausts	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Projector LED	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Solenoid bell	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Soldering iron	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric Drill	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm

## RESPONSE CHARACTERISTICS

Fuel	Size	Sensitivity	Distance ft. (m)
H <sub>2</sub>	32-in Plume	Extreme	98 (30)
H <sub>2</sub>	32-in Plume	Medium	66 (20)
H <sub>2</sub>	32-in Plume	Low	33 (10)
Methanol	1 x 1 ft.	Extreme	59 (18)
Methanol	1 x 1 ft.	Medium	30 (9)

Fire Protection Technologies Pty Ltd  
 Melbourne : Sydney : Brisbane : Perth : Auckland : Singapore  
 Head Office: 1/251 Ferntree Gully Road, PO Box 75, Mt Waverley, VIC 3149 ABN: 69 634 309 461 PH: 1300 742 296