

IR3-H2-HD Triple IR Hydrogen Flame Detector

The IR3-H2-HD flame detector provides ultra-fast response, high performance and reliable detection of hydrogen (H₂) fires. The detector addresses slow growing fires as well as fast eruptions of fire using improved IR3 technology. The detector operates in all weather and light conditions.

In addition, the detector provides high-definition (HD) video output of the monitored area with clear imaging of a fire event and of personnel at distances up to 100 ft. (30m). This allows the rescue team to be aware of the exact situation before entering the hazardous area. The detector automatically records video of fire event (1 minute pre- and up to 3 minutes post-alarm initiation). These features, along with the built-in event logger, provide additional means to study the cause and development of fire events.



KEY BENEFITS

- High immunity to false alarm
- Ultra-fast detection mode detection within 40 milliseconds for Hydrogen fireballs or explosions
- Hydrogen flame detection
- High sensitivity – up to 100 ft. (30m)
- HD video output with Automatic HD video recording of fire events
- Data/Event logger – alarms, faults and other relevant events are logged to non-volatile memory
- Ethernet communication – in addition to the standard methods, such as 4-20mA and Modbus
- Built-in-Test (BIT) – Automatic and manual internal self-test of window cleanliness and the overall operation of the detector
- Window heater to avoid condensation and icing
- Stainless steel tilt mount with horizontal and vertical adjustment. Optional mounting adapters available for retrofit installation

ORDERING

FIK-IR3-H2-HD-AS11¹	Detector, HD video output, M25 conduit openings
FIK-IR3-H2-HD-AS21¹	Detector, HD video output, ¾" NPT conduit openings
FIK-TMO-S02²	Tilt Mount, Stainless Steel (shown above)
FIK-FSIM-IR3-H2-KIT²	Flame Simulator Kit
FIK-USB/RS485^{2,3}	RS-485 to USB Converter Kit
FIK-WCO-S02^{2,4}	Weather Cover, Stainless Steel

¹ATEX, EA CU TR, SIL 2 and HART 7 models available. Contact Fike at 1-800-979-3453 for ordering information

²Ordered separately

³Converts detector RS-485 communication network to USB for connection to a computer port.

⁴Used only in very hot or very cold environments.

SPECIFICATIONS

FIRE DETECTION	Detection time and distance	40ms for fast burst of explosion 1.5s for 32" (0.8m) hydrogen fire at 0-66 ft. (0-20m) 4s for 32" (0.8m) hydrogen fire at 66-100 ft. (20-30m)
	Field of view (IR detection)	90° Horizontal, 75° Vertical
	Time Delay	0-30 seconds (adjustable)
	Built in Test	Automatic or Manual
VIDEO FUNCTIONALITY	HD Video	Near IR filtered imaging of fire and people at 100 ft. (30m) distance
	Video recording of alarm events	1-minute pre-event and 3 minutes post-event
	System integration protocol	ONVIF (Open Network Video Interface Forum) Profile S
ELECTRICAL SPECIFICATIONS	Operating Voltage	24 VDC nominal (18-32 VDC)
	Current Consumption	Standby: 180mA Maximum: 250mA all systems in operation (including window heater)
	Conduit Entries	2x cable and conduit entries ¾" 14NPT or M25x1.5
	Wiring	12-20AWG (2.5-0.35mm ²)
OUTPUTS	Relays	SPST volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	0-20mA (stepped) current output	3 wire and 4 wire configurations (sink and source)
	Indication	Tri-color LED (Green, Yellow, Red)
	Modbus	RTU compatible on RS-485
	Digital (for video)	IP network IEEE 802.3 10Base-t
	Composite video	NTSC or PAL
MECHANICAL SPECIFICATIONS	Size	7.87 x 5.12 x 5.12" (200 x 130 x 130 mm)
	Weight	Detector (stainless steel 316): 9.8 lbs. (4.4 kg) Tilt mount (stainless steel 316): 5.4 lbs. (2.4 kg)
ENVIRONMENTAL SPECIFICATIONS	Temperature Range	Operating: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	Humidity	Up to 99% (RH), non-condensing
	Ingress Protection	IP66 & 68; NEMA 4X & 6P
APPROVALS	IECEX	Ex db IIB T5 Gb -50°C ≤ Ta ≤ 75°C Ex db IIB T4 Gb -50°C ≤ Ta ≤ 85°C
	FMus & FMc	Class I, Div. 1, Groups B, C & D: T4 T4 -50°C ≤ Ta ≤ 85°C T5 -50°C ≤ Ta ≤ 75°C
	Performance	ANSI FM 3260
WARRANTY	5 Years	

IMMUNITY TO FALSE ALARMS

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric arc	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Arc welding	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Radiation heater, 1850W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (1000W) shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Quartz lamp (500W) non-shielded	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Exhausts	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Projector LED	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Solenoid bell	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Soldering iron	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric Drill	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm

RESPONSE CHARACTERISTICS

Fuel	Size	Sensitivity	Distance ft. (m)	Average Response Time (Sec)
H ₂	32-in Plume	Extreme	98 (30)	4.0
H ₂	32-in Plume	Medium	66 (20)	1.6
H ₂	32-in Plume	Low	33 (10)	1.5
Methanol	1 x 1 ft.	Extreme	59 (18)	4.3
Methanol	1 x 1 ft.	Medium	30 (9)	1.6

Fire Protection Technologies Pty Ltd
 Melbourne : Sydney : Brisbane : Perth : Auckland : Singapore
 Head Office: 1/251 Ferntree Gully Road, PO Box 75, Mt Waverley, VIC 3149 ABN: 69 634 309 461 PH: 1300 742 296