

IR3-H2-HD Triple IR Hydrogen Flame Detector

The IR3-H2-HD flame detector provides an ultra-fast response, high performance, and reliable detection for a number of fires found in Energy Transition applications. The detector addresses slow-growing fires as well as fast eruptions of fire using improved IR3 technology. The detector operates in all weather and light conditions.

The detector provides high-definition (HD) video output of the monitored area with clear imaging of a fire event and personnel at distances up to 100 ft. (30m). This allows the rescue team to be aware of the exact situation before entering the hazardous area. Video and data of events are stored and saved quickly to non-volatile memory for post-incident investigation. The recordings start one minute before detection and continue for up to four minutes.

KEY BENEFITS

- High immunity to false alarms, including arc welding
- Ultra-fast detection mode detection within 40 milliseconds for Hydrogen fireballs or explosions
- Detects hydrogen, ammonia, methane & Syngas flames: 3 infrared wavelengths with clear separation
- Five selectable sensitivity levels
- HD or composite video output with automatic HD video recording of events
- Data/Event logger – alarms, faults, and other relevant events are logged to non-volatile memory
- Universal outputs, 3 and 4 wire, 4-20 mA sink/source, Fire, Auxiliary, and Fault Relays, RS485 port using Modbus RTU
- Built-in-Test (BIT) – Automatic and manual self-test of window cleanliness and overall detector operation
- Window heater to avoid condensation and icing
- Stainless steel tilt mount, adjustable horizontally/vertically



ORDERING

FIK-IR3-H2-HD-AS11	IR3 Hydrogen Flame Detector, SS316, 2 x M25 entries, Near IR VID, standard configuration
FIK-IR3-H2-HD-AS11-H	IR3 Hydrogen Flame Detector, SS316, 2 x M25 entries, Near IR VID, process industry (SIL 2 – HART®)
FIK-IR3-H2-HD-AS21	IR3 Hydrogen Flame Detector, SS316, 2 x 3/4" NPT entries, Near IR VID, standard configuration
FIK-IR3-H2-HD-AS21-H	IR3 Hydrogen Flame Detector, SS316, 2 x 3/4" NPT entries, Near IR VID, process industry (SIL 2 - HART®)
FIK-IR3-H2-HD-AS12	IR3 Hydrogen Flame Detector, SS316, 2 x M25 entries, Color VID (SIL 2-HART®)
FIK-IR3-H2-HD-AS22	IR3 Hydrogen Flame Detector, SS316, 2 x 3/4" NPT entries, Color VID (SIL 2-HART®)
FIK-IR3-H2-HD-AS15	IR3 Hydrogen Flame Detector, SS316, 2 x M25 entries, Near IR VID, NFPA 33 (SIL 2-HART®) ¹
FIK-IR3-H2-HD-AS25	IR3 Hydrogen Flame Detector, SS316, 2 x 3/4"NPT entries, Near IR VID, NFPA 33 (SIL 2-HART®) ¹
ACCESSORIES	
FIK-TMO-S02	Tilt Mount, SS316, HD Detector (shown above)
FIK-WCO-S02	Weather Cover, SS316, HD Detector
FIK-PMA-S23	Pole Mount Adapter, 2 and 3 inch
FIK-PMA-S06	Pole Mount Adapter, 6 inch
FIK-ASD-S02	AIRSHIELD, HD Detector ²
FIK-FSIM-IR3-H2-KIT	Flame Simulator Kit, IR3-H2 Detector
FIK-USB/RS485	USB/RS485 Converter Kit ³

^[1] Automotive / Spray booth

^[2] Provides protection against dust, snow and other interferences.

^[3] For PC/Laptop USB port. Includes FLS Flame Detector Communicator software.

SPECIFICATIONS

FIRE DETECTION	Detection time and distance	40ms for fast burst or explosion 1.5s for 32" (0.8m) hydrogen fire at 0-66 ft. (0-20m) 4s for 32" (0.8m) hydrogen fire at 66-100 ft. (20-30m)
	Sensitivity Range	5 sensitivity ranges: Extreme, High, Medium, Low, Very Low
	Field of view (IR detection)	90° Horizontal, 75° Vertical
	Time Delay	0-30 seconds (adjustable)
	Built in Test	Automatic and Manual
VIDEO FUNCTIONALITY	HD Video	Near-IR filtered HD, as standard. Color HD option (X2 available on request).
	Video recording of alarm events	1-minute pre-event and up to 3 minutes post-event
	System integration protocol	ONVIF (Open Network Video Interface Forum) Profile S
ELECTRICAL SPECIFICATIONS	Operating Voltage	24 VDC nominal (18-32 VDC)
	Current Consumption	Standby: 180mA Maximum: 300mA all systems in operation (including window heater)
	Conduit Entries	2x cable and conduit entries 3/4" NPT(F) or M25x1.5
	Wiring	12-20AWG (4.0-0.50mm ²)
OUTPUTS	Relays	SPST volt-free contacts rated 2A at 30 VDC Alarm – normally open Auxiliary – normally open Fault – normally closed
	0-20mA (stepped) current output	3 wire and 4 wire configurations (sink and source) HART® rev 7.0 (option available)
	Indication	Tri-color LED (Green, Yellow, Red)
	Modbus	RTU compatible on RS-485
	Digital (for video)	IP network IEEE 802.3 10Base-T
	Composite video	NTSC or PAL
	MECHANICAL SPECIFICATIONS	Size
	Weight	Detector (stainless steel 316): 9.8 lbs. (4.4 kg) Tilt mount (stainless steel 316): 5.4 lbs. (2.4 kg)
ENVIRONMENTAL SPECIFICATIONS	Temperature Range	Operating: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	Humidity	Up to 99% (RH), non-condensing
	Ingress Protection	IP66 & 68; NEMA 4X & 6P
APPROVALS	ATEX	ATEX: II 2 G D Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	IECEX	Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	FMus & FMc	Class I, Div. 1, Groups B, C & D; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C Class II/III, Div. 1, Groups E, F, G; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C Class I, Zone 1, AEx/Ex db IIC T4 Gb or Class I, Zone 1, AEx/Ex db eb IIC T4 Gb -50°C≤Ta≤85°C Class I, Zone 1, AEx/Ex db IIC T5 Gb or Class I, Zone 1, AEx/Ex db eb IIC T5 Gb -50°C≤Ta≤75°C Zone 21, AEx/Ex tb IIIC T95°C Db -50°C≤Ta≤75°C or Zone 21, AEx/Ex tb IIIC T105°C Db -50°C≤Ta≤85°C
	Performance	ANSI FM3260
	Functional Safety	Complies with SIL2, per IEC 61508 (option available)
	CSFM	Listing 7210-2010:0524
	WARRANTY	5 Years

IMMUNITY TO FALSE ALARMS AT EXTREME SENSITIVITY (modulated/unmodulated)

False Alarm Source	Maximum Distance in ft. (m)
Sunlight, Direct, Reflected	No response at any distance
Sunlight, Direct, Reflected, with water drops on sensors	No response at any distance
Incandescent frosted glass light, 300W	2.0 (0.5)
Fluorescent, 70W (3x23.3W)	2.0 (0.5)
Electric arc	3.0 (1.0)
Arc welding	2.0 (0.5)
Radiation heater, 1850W	2.0 (0.5)
Radiation Heater, 1850W with water droplets on sensors	2.0 (0.5)
Quartz lamp (1000W) shielded	2.0 (0.5)
Quartz lamp (500W) non-shielded	2.0 (0.5)
Quartz lamp (500W) non-shielded with water drops on sensors	2.0 (0.5)
Mercury vapor lamp 160Wx3	2.0 (0.5)
Car Exhausts	2.0 (0.5)
Projector LED	2.0 (0.5)
Solenoid bell	2.0 (0.5)
Soldering iron	2.0 (0.5)
Electric Drill	2.0 (0.5)

IR3-H2-HD RESPONSE CHARACTERISTICS (Standard Models, X1 & X2)

Fuel	Size	Sensitivity	Distance ft. (m)	Average Response Time (Sec)
Hydrogen (H ₂)	32-in Plume	Extreme	98 (30)	1.5
Hydrogen (H ₂)	32-in Plume	Medium	66 (20)	1.5
Hydrogen (H ₂)	32-in Plume	Low	66 (20)	1.4
Hydrogen (H ₂)	32-in Plume	Very Low	16 (5)	1.3
Methanol	1 x 1 ft.	Extreme	59 (18)	4.2
Methanol	1 x 1 ft.	Medium	30 (9)	2.9
Methanol	1 x 1 ft.	Very Low	10 (3)	3.6
Methane	32-in Plume	Extreme	66 (20)	1.7
Methane	32-in Plume	Medium	66 (20)	0.9
Methane	32-in Plume	Low	66 (20)	1.1
Methane	32-in Plume	Very Low	13 (4)	0.8
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Extreme	82 (25)	3.6
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Medium	82 (25)	2.8
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Low	82 (25)	1.1
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Very Low	13 (4)	2.2

For performance details of model 5, the following document is available on request:

- Model 5 provides fast response for enclosed space/automotive/spray paint booth applications, see document F101V0024.06.

PRODUCTS:

Gaseous Suppression



Inert Gas (IG-01, IG-55, IG-100, IG-541)
Novec 1230™ Fluid (FK-5-1-12)
FM-200® (HFC-227ea.)
Carbon Dioxide (CO₂)
Hybrid Systems (N₂ / Water)
Pressure Relief Vents
Enclosure Integrity Testing Equipment
Pipe & Fittings

Water Suppression



Water Mist - High Pressure
Water Mist - Intermediate Pressure
Water Mist - Low Pressure
Hybrid Systems (Water / N₂)
Monitors & Delivery Systems
High Speed Deluge

Foam Suppression



Foam Concentrates
Foam Proportioning
Foam Delivery Systems
Compressed Air Foam
Foam Concentrate Testing

Explosion Protection



Explosion Suppression
Explosion Isolation
Explosion Vents & Pressure Relief
Spark Suppression
Explosibility Testing

Fire Detection



Linear Heat Detection - Digital
Linear Heat Detection - Fibre Optic
Linear Heat Detection - Micro Chip
Flame Detection
Video Imaging Detection
Spark Detection
Control & Indicating Equipment
Thermal Imaging Detection
Aspirating Smoke Detection

Military & Defence



Military Vehicles
Naval Vessels

Special Applications



Micro Environment
Oxygen Reduction
Kitchen Protection Systems
Dry Chemical
Vehicle Systems
Marine & Offshore
Vapour Mitigation
Li-Ion Fire Systems

Support Services



Design / Engineering
Technical Support
Services & Testing

Australia

Head Office

Unit 1, 251 Ferntree Gully Road
Mt Waverley VIC 3149
Australia

Brisbane Office

Unit 7, 93 Rivergate Place
Murarrie QLD 4172
Australia

Perth Office

18 – 20 Ledgar Road
Balcatta WA 6021
Australia

Sydney Office

Unit 5, 11 Reliance drive Tuggerah
NSW 2259
Australia

1300 742 296

www.fire-protection.com.au
enquiries@fire-protection.com.au

New Zealand

Auckland Office

Unit 2, 13 Airborne Road
Albany North Shore 0632
New Zealand

0011 64 9415 5488

www.fire-protection.net.nz



‘Every solution for your special hazard problems’